



## Data Sheet 4541138

**Product:** Plus WL bryter 4k dim I SO  
**EI-number:** 4541138  
**Mat.no:** EKO04250  
**EAN:** 7020160425010  
**Packing:** 1  
**Color:** Black



**Product description:** ELKO Wireless switch 4ch dim is a combiunit with switch and dimmer integrated. Max load on the dimmer is 250W ohmic load. The integrated dimmer is controlled by two of the buttons on the switch or via other WL switches in the system. The combiunit has 4 pushbuttons and can control relays, dimmers or activate different scenarios in addition to control the integrated dimmer. It can be mounted in regular flush mounted boxes or in surface housings.

---

**Technical specifications:** Radiofrequency: 868MHz, GFSK-modulation, data rate 2,4 kbps.  
Range: 300 m outdoors, 10-50 m indoors.

**SWITCH :**

Battery type: CR2032 (included).  
Battery lifetime: 5-10 years or 40 000 operations.  
Degree of protection: IP20.

**DIMMER:**

Degree of protection: IP20.  
Max load:  
20-250VA lightbulbs, electronic or iron trafos.  
Overloadprotection  
Electronic temperaturefuse and shortcircuit fuse with auto reset.  
Thermofuse release at 115°C - no reset.  
Screwless termination for 2x 2,5 mm<sup>2</sup> cable  
Color: Black


### ELKO AS

E-mail: elko@elko.no  
Internet: www.elko.no  
Bank: 6219.05.15880  
Org.no.: NO 911 382 563 MVA


ELKO Front office  
Sandstuveien 68, NO-0680 Oslo  
P.O.Box 6598 Etterstad, NO-0607 Oslo  
Tel.: +47 67 80 73 00  
Fax: +47 67 80 73 01

ELKO Plant  
Sporpind Industriområde, NO-3340 Åmot  
Tel.: +47 32 78 91 00  
Fax: +47 32 78 91 01

## Size



## Wiring diagram



## ELKO AS

E-mail: [elko@elko.no](mailto:elko@elko.no)  
Internet: [www.elko.no](http://www.elko.no)  
Bank: 6219.05.15880  
Org.no.: NO 911 382 563 MVA

ELKO Front office  
Sandstuveien 68, NO-0680 Oslo  
P.O.Box 6598 Etterstad, NO-0607 Oslo  
Tel.: +47 67 80 73 00  
Fax: +47 67 80 73 01

ELKO Plant  
Sporpind Industriområde, NO-3340 Åmot  
Tel.: +47 32 78 91 00  
Fax: +47 32 78 91 01