




Data Sheet 1410712


Product: Plus BRYTER INNFELT 5 ALU
EI-number: 1410712
Mat.no: EKO03740
EAN: 7020160374011
Packing: 5
Color: Aluminium




Product description: Flush mounted rocker switch 2 times 1 pole common L (two-circuit (two-rockers)) in ELKO Plus design. The switchbases have screw terminals, wiring diagram printed on the rear side. Push-button function is possible by use of a spring (T 47) under the rocker. Pilot-lamp (S 740) for light use is possible by replacing rocker by windowrocker(L 608). Thermoplastic in the rocker and coverplate.

Technical specifications: Flush mounted Rocker switch, Two-circuit - one common L.
Screw terminals.
Flush wiring, thermoplastic rocker.
16A / 250VAC
IP 20.
Color: Aluminium
Halogenfree.
C-C distance: 60 mm
Conduit connection length: 8mm
Amount of conduits pr terminal: 2
Maximum torque: 0,8Nm (According to IEC 62196-1)
Maximum cross section: 4mm²
Depth: 11,5mm.

Size



Wiring diagram



ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporvind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01