




Data Sheet 3088261

Product: LED DL tilt 7W 2700K Alu
EI-number: 3088261
Mat.no: EKO06971
EAN: 7020160697110
Packing: 1
Color:



Product description: ELKO Bright tilt-downlight is a adjustable lowprofile downlight with a good luminous efficacy. The downlight is tiltable in two directions. The special encapsulation gives you the possibility to install the downlight directly into a isolated ceiling. No box is necessary. The LED driver is specially adapted to the ELKO 315GLE dimmer and gives great performance in the lower brightness levels. Delivered with colortemperature 2700K, and in Polarwhite, Aluminium and Black colors.

Technical specifications: LED downlight recessed installation
Can be adjusted in two directions.
Voltage: 230V / 50Hz
System effect: 7W
Light color: 2700K
Light spread: 36°
Lumious efficacy: 565 Lumen
Light distribution: 652Cd
CRI/Ra>85
Cutout: 83mm
Degree of protection: IP44
Depth: 48mm - fits in 2 beams.
Lifetime 50.000 hours- L70
Isolation safe - can be installed directly in isolation.
Quick connection on drivercable - opportunity to terminate the driver an remove the lamp to paint the ceiling
4 screwless terminals in the connectionbox.
Color: RAL9006 - Aluminium

ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporvind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01

ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01