




Data Sheet 4540035

Product: SmartSwitch Push 10A Plus ALU
EI-number: 4540035
Mat.no: EKO06998
EAN: 27020160699804
Packing: 1
Color:



Product description: SmartSwitch push is a digital switch to control up to 10A of ohmic, inductive or capacitive loads directly on the button or be controlled via the ELKO Smart App. It can also be used to trigger moments or automations set in the ELKO Smart App.

Technical specifications: Voltage: 230V AC / 50 Hz
Standby: Max. 0,4W
Nominal current: 10A, $\cos\phi=0,6$
Fuse protection: 16A Circuit breaker
Frequency band: 2,4 GHz
Transmission capacity: Max. 2,5 mW
IP degree: IP20
Operating temperature: 0°C - 35°C
Communication protocol: Zigbee 3.0
Connecting terminals: Screw terminals 2x2,5mm² solid or stranded types
Torque: 0,5Nm
Extension units: Mechanical single push-buttons (unlimited)
Electronic overload protection
Overheating protection
Short-circuit protection
Soft start

LED: 200W
Incandescent lamps: 220W
230V Halogen lamps: 14-150W
Electronic transformer: 14-150VA
Capacitive loads: 10A 140 μ F
Energy saving lamps: 200W
Motor single phase 230V: 1000VA

ELKO AS


E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01

Size

Wiring diagram



ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01