



## Data Sheet 4540096

**Product:** SmartSocket Double 16A Plus BLCK  
**EI-number:** 4540096  
**Mat.no:** EKO09741  
**EAN:** 17020160974102  
**Packing:** 5  
**Color:** Black



### Product description:

The SmartSocket Double 16A is a combination of one connected and one regular (non-connected) electrical outlet designed to manage and control electrical devices in a convenient and efficient manner. LED indicator and clear markings are available inside and on the top of the connected socket for easy identification. Fully integrated with the ELKO Smart System, the double socket-outlet can be used for a variety of applications including remote ON/OFF, power monitoring, scheduling, automation and much more. The double socket-outlet fits in regular depth wall boxes and does not require any special installation compared to regular socket outlets making it convenient to fit in any kind of new or existing installation. The SmartSocket Double 16A has clear markings and LED indication for easy identification of the connected socket outlet.

### Control options:

Home control: With ELKO SmartHUB, you can control the electrical devices with the connected double socket outlet remotely through the ELKO Smart app, moments and automations, wireless switch or through Voice (Amazon Alexa, Google Home).

Direct operation: The socket operation can always be controlled directly through the push button on the connected socket device.

### Functions:

? The SmartSocket Double 16A has clear markings and LED indication for easy identification of the connected socket outlet.

The SmartSocket Double 16A offer much more than a normal socket outlet when used with the ELKO Smart app including:

? Switching devices ON/ OFF, and checking the status from the socket or remotely via app.

? Setting a timer or a schedule (via app).

? Monitor and control energy consumption of connected loads with a high level of accuracy (1% for loads > 25 W) via app.

? Creating moments and automation with other ELKO Smart Home products.

### ELKO AS

E-mail: [elko@elko.no](mailto:elko@elko.no)  
Internet: [www.elko.no](http://www.elko.no)  
Bank: 6219.05.15880  
Org.no.: NO 911 382 563 MVA

ELKO Front office  
Sandstuveien 68, NO-0680 Oslo  
P.O.Box 6598 Etterstad, NO-0607 Oslo  
Tel.: +47 67 80 73 00  
Fax: +47 67 80 73 01

ELKO Plant  
Sporpind Industriområde, NO-3340 Åmot  
Tel.: +47 32 78 91 00  
Fax: +47 32 78 91 01

---

**Technical specifications:** Nominal voltage: AC 230 V ~, 50 Hz  
Standby: max. 0.4 W  
Fuse protection: 16 A miniature circuit breaker  
Operating frequency: 2405-2480 MHz  
Max. radio-frequency power transmitted: < 10 mW  
Protection: IP20  
Measuring accuracy:  $\pm 1\%$  for loads >25 W  
Communication protocol: Zigbee 3.0 certified

---

Size

Wiring diagram

#### ELKO AS

E-mail: [elko@elko.no](mailto:elko@elko.no)  
Internet: [www.elko.no](http://www.elko.no)  
Bank: 6219.05.15880  
Org.no.: NO 911 382 563 MVA

ELKO Front office  
Sandstuveien 68, NO-0680 Oslo  
P.O.Box 6598 Etterstad, NO-0607 Oslo  
Tel.: +47 67 80 73 00  
Fax: +47 67 80 73 01

ELKO Plant  
Sporpind Industriområde, NO-3340 Åmot  
Tel.: +47 32 78 91 00  
Fax: +47 32 78 91 01