



Data Sheet 4523410

Product: ESH Plus 316GLED dimmer RF PW
EI-number: 4523410
Mat.no: EKO05821
EAN: 7020160582119
Packing: 1
Color:



Product description:

ESH 316GLED RF dimmer is a part of the ELKO Smart Home system. Dimmers and other components are communication to the ELKO Gateway internally with the Zigbee protocol. The ESH components are controlled by the Gateway, which is controlled by the ESH App on mobile devices. 316GLED RF is designed to operate even if the wireless network fails, the dimmer will then function in Stand alone mode, with local physical operation. It is also possible to control the dimmer with a remote controlled switch. This can be programmed with or without a Gateway. The Gateway must be installed and programmed if you want to control your home with an app.

316 GLED dimmer is developed for LED and low loads. It also works with ohmic loads, electronic trafos and 230V Halogen loads. ELKO Plus version is delivered with an integrated light guide for pilot lamp around the dimmer knob. The light can be turned on/off in the menu.

The dimmer must be connected to both L and N, and can be used as 1 pole as well as 2 pole.

Choose between GLI or GLE mode (leading- and trailing edge dimming), makes the dimmer extremely flexible.

The startlevel can be adjusted so the LED lamps starts, minimum- and maximum brightness level can easily be adjusted.

316GLED is very slim and is only 24mm into the box, it will fit in surface boxes and in every ELKO combination plates.

ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01

